

Biaxial fabric data sheet

Code # C1000X

Characteristics									
		Nominal		Tolerance					
Mass per unit of area	(g/m²)	987		± 5%					
Construction		Biaxial +45/							
		+45	-45	0					
Fabric description		Carbon fiber 24K	Carbon fiber 24K	E-Glass					
Fabric gauge	(gg)	5.5	5.5	1					
Fabric distribution	(g/m²)	490	490	3					

49.65%

0.3

49.65%

Stitching fiber						
Stitching thread		Texturized Polyester (black)				
Stitch DTex		35				
Stitch gauge	(gg)	6.0				
Stitch length	(mm)	2.50				
Stitch type		Tricot				
Stitch weight	(g/m²)	3				

Note: Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

111111111	1 1	11111111111111111111111111111111111111	2	1111111	3
	2 3	cm 4	5	6 7	8 9
		11		M	

SALES & ORDER PROCESSING 28th of October St No 8A, 37300 Agria, Greece, EU

Weight rate

(%)

EU ORDERING INFO Tel: +30 24280 92210 Email: sales@fibermax.eu Head office: Fibremax Ltd 35 Grafton Way, W1T 5DB London, UK