


Balanced woven fabric data sheet

Code # CP260Tr

Characteristics				
		Nominal	Tolerance	
Mass per unit of area	(gr/sqm)	257	± 5%	
Weave		Twill 2X2		
Laminate thickness	(mm)	0,25	± 5%	

Warp – Weft ratio				
		Warp	Weft	
Fiber description		HS carbon fiber TR30S 3K	HS carbon fiber TR30S 3K	
			Polyester fiber (red) -122	
Thread count	(ends/cm)	7	Carbon 3,8	
			Polyester 3,8	
Weight distribution	(gr/sqm)	140	Carbon 75	
			Polyester 42	
Weight distribution	(%)	54	Carbon 29	
			Polyester 16	
Total weight rate	(%)	54	46	

Note: Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.



SALES & ORDER PROCESSING 28th of October St No 8A, 37300 Agria, Greece, EU EU ORDERING INFO Tel: +302428092210 Email: sales@fibermaxcomposites.com Head office: Fibremax Ltd 35 Grafton Way, W1T 5DB London, UK